

## CRD15

Cradle for H15



### + Specifications

#### Communication

- USB: Ver. 1.1, client, VCP, USB-A connector

#### Power

- Voltage requirement: 6 V DC
- Battery charging time: Ca. 3 hours

#### Physical

- Dimensions (w x h x d):  
72 x 75 x 115 mm / 2.83 x 2.95 x 4.53 in
- Weight body: Ca. 180 g / 6.3 oz
- Case: ABS, Black

#### Regulatory & Safety

- Product compliance: CE incl. LVD, FCC, cUL, RoHS

#### Enclosed items

- USB cable
- Power supply 6V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang

Opticon Sensors Europe B.V.  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com

# OPTICON

WWW.OPTICON.COM