

IRU8000

Cradle for PHL8000 series



+ Specifications

Communication

- RS232: Full function support
- USB: Ver. 1.1, USB-A connector

Power

- Voltage requirement: 5 V DC
- Battery charging time: Standard battery pack Ca. 3 hours, High-capacity battery pack Ca. 6 hours

Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Drop test: 0.75 m / 2.5 ft drop onto concrete surface

Physical

- Dimensions (w x h x d): 134 x 58 x 141 mm / 5.28 x 2.28 x 5.55 in
- Weight body: 475 g / 1 lbs 0.8 oz
- Case: ABS, Black

Regulatory & Safety

- Product compliance: CE incl. LVD, FCC, cUL, RoHS

Enclosed items

- USB cable

Sold separately

- RS232 cable
- Power supply 5V/2.6A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang

Opticon Sensors Europe B.V.
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON

WWW.OPTICON.COM